

PeakTech® 1090 PROD-ID: P 1090

[BACK](#)

AC/DC Voltage Tester with RCD-Test and LCD-display

This TÜV/GS approved, 2-pole voltage tester provides a backlight LCD display and bargraph for AC - and DC measurement from 6 V to 690 V. Additionally it offers the possibility of continuity test with visual and audible signal, phase and direction indicator, and the testing of residual current devices (RCD).

- Self-test function
- AC/DC-voltage detection
- Polarity detection
- Single-pole phase test and rotary field indication
- Low impedance test function for residual current devices (RCD)
- Integrated flashlight
- IP 64 protection against dust and splashing water
- Safety: EN 61243-3; TÜV/GS; CAT III 690 V/ CAT IV 600 V
- Accessories: carrying case, batteries and manual



MANUAL

[PeakTech 1090-1095 03-2019F.pdf \(1,081.5 kB\)](#)

PICTURES

[1090_F_Freigestellt.jpg \(194.9 kB\)](#)

[1090_L_Freigestellt.jpg \(197.6 kB\)](#)

[1090_R_Freigestellt.jpg \(201.6 kB\)](#)

Display	3 1/2 digit LCD-Display, max. 1999, with bargraph and backlight
Voltage range	6/12/24/50/120/230/400 V AC/DC; 690 V DC
Resolution	1 V AC/DC
Accuracy	DCV: +/- 1,0 % + 3 dgt. / ACV: +/- 1,5 % + 5 dgt.
Voltage frequency range	50/60 Hz
Operation voltage	2 x 1,5V AAA batteries
Dimensions (WxHxD)	52 x 255 x 40 mm
Weight	215g
EAN-13	4250569400889

