

Triple Output Programmable DC Power Supply

Model 9129B



The 9129B is an economical triple output linear programmable DC power supply featuring isolated outputs that can be adjusted independently or combined in series or parallel to output higher voltage or current. Additionally, this supply can operate in tracking mode with user-configurable ratios between channels.

The front panel keys and rotary knob with convenient cursors let users quickly set voltage and current values. Up to 27 different instrument settings can be saved and recalled. The power-on state of the outputs can also be configured.

The USB to TTL interface supporting SCPI commands can be used to remotely control the power supply via a PC. Alternatively, users can control the 9129B, execute test sequences or log measurements using the provided PC software application. This software also integrates with Data Dashboard for LabVIEW apps enabling iOS, Android, or Windows 8 compatible tablets or smartphones to remotely monitor select measurement indicators.


This power supply is suitable for a wide range of applications including education, service and electronic design.

Features


- Three independent and electrically isolated outputs
- Displays voltage and current settings for all three channels simultaneously
- Low noise, linear regulation
- Series and parallel modes combine channels to increase the output voltage or current
- Tracking mode allows users to set up channels to maintain a programmed ratio
- Fully programmable channels with output On/Off control
- Store and recall up to 27 instrument settings
- Communicate via USB interface supporting SCPI commands using the included USB to TTL serial adapter
- Softpanel for remote control, test sequence generation, and datalogging available
- Overvoltage (OVP) and overtemperature (OTP) protection including keylock function
- Compact 19" half-rack form factor allows for side-by-side rack mounting of two units

Output Rating	
Voltage	0 - 30 V (CH1 & CH2) 0 - 5 V (CH3)
Current	0-3 A (CH1, CH2 & CH3)

Front panel



Rear panel



Flexible operation

Combined series mode




Channels 1 and 2 can be wired in series to increase the voltage. Selecting series combined mode provides convenient metering of the channels connected in series.

Combined parallel mode



Channels 1 and 2 can be wired in parallel to increase the current. Selecting parallel combined mode provides convenient metering of the channels connected in parallel.

Tracking mode




Tracking mode can be used to simplify adjustments across multiple channels by maintaining a user-defined ratio between outputs. Tracking mode can be set on channels 1 and 2.

Application software



Bipolar output configuration

The independent and isolated outputs can be used to create positive and negative outputs between channels 1 and 2.



This feature is useful for powering bipolar circuits and devices.

PC software is provided for front panel emulation, generating and executing test sequences or logging measurement data without the need to write source code.

- Remote monitoring on iOS, Android, or Windows 8 compatible tablets or smartphones via NI Data Dashboard for LabVIEW apps.
- Log voltage, current, and power values of each channel as well as timestamp, CV/CC mode, and output status.
- Quickly develop a custom dashboard with indicators, charts, or gauges to monitor your power supply.
- Create an unlimited number of external list files to be executed from PC memory. Save and recall list files to/from the PC.

Specifications

Model		9129B
Output Rating		
Voltage		0–30 V (CH1 & CH2), 0–5 V (CH3)
Current		0–3 A (all channels)
Power		195 W
Load Regulation		
Voltage		$\leq 0.02\% + 4\text{ mV}$
Current		$\leq 0.2\% + 3\text{ mA}$
Line Regulation		
Voltage		$\leq 0.02\% + 4\text{ mV}$
Current		$\leq 0.2\% + 3\text{ mA}$
Ripple & Noise		
Voltage		$\leq 5\text{ mVp-p} / \leq 1\text{ mVrms}$
Current		$\leq 6\text{ mArms}$
Programming Resolution		
Voltage		10 mV
Current		1 mA
Readback Resolution		
Voltage		10 mV
Current		1 mA
Programming Accuracy $\pm$ (% output + offset)		
Voltage		$\leq 0.06\% + 20\text{ mV}$
Current		$\leq 0.2\% + 10\text{ mA}$
Readback Accuracy $\pm$ (% output + offset)		
Voltage		$\leq 0.06\% + 20\text{ mV}$
Current		$\leq 0.2\% + 10\text{ mA}$
Series Accuracy (combined mode)		
Voltage		$\leq 0.5\% + 30\text{ mV}$
Current		$\leq 0.2\% + 15\text{ mA}$
Parallel Accuracy (combined mode)		
Voltage		$\leq 0.2\% + 30\text{ mV}$
Current		$\leq 0.2\% + 25\text{ mA}$
General		
Memory		3 memory groups with 9 locations in each group
Remote Interface		USB (Virtual COM via included USB to TTL serial adapter)
AC Input		110/220 VAC (+/- 10 %), 47 Hz - 63 Hz
Operating Temperature		32 °F to 104 °F (0 °C to 40 °C), relative humidity up to 80%
Storage Temperature		-4 °F to 158 °F (-20 °C to 70 °C)
Dimensions (W x H x D)		8.45" x 3.47" x 13.96" (214.5 x 88.2 x 354.6 mm)
Weight		16.05 lbs. (7.3 kg)
Three-Year Warranty		
Standard Accessories		Power cord, IT-E132B (USB to TTL serial adapter plus USB cable), test report, and certificate of calibration
Optional Accessories		IT-E151 rack mount kit

Note: All specifications apply to the unit after a temperature stabilization time of 15 minutes over an ambient temperature range of 23 °C $\pm$ 5 °C.